

사양/SPECIFICATIONS

	Items	Unit	YGS-2510CNC	YGS-3010CNC	YGS-2510CNC
	Max. Grinding Dimensions (Length × Width × Height)	mm	2500 × 1020 × 710	3000 × 1020 × 710	2500 × 1020 × 710
면의 크기	Working area of table(W × L)	mm	2650 × 1020	3150 × 1020	2650 × 1020
까지의 높이	Height from floor to table surface	mm	852		
	Distance Between Columns	mm	1350		
속도	Feed speed of table	m / min	4 - 30		
대행정	Max. travel of table	mm	2900	3400	2900
이블 상면	Distance of table surface to wheel face	mm	0-710		
리	Head longitudinal travel	mm	1450		
에서 조작자 이송거리	To the side operator from center of table	mm	725		
에서 방향으로의	To the opposite side to operator from center of table	mm	725		
	Wheel size(Dia. × Width × Bore)	mm	φ 510 × 100 × φ 203.2		
스	Spindle speed	rpm	980		
정	Head Vertical travel	mm	710		
직이송	Min.feed(vertical)	mm	0.001		
	Spindle motor	Kw / p	15 / 6		
터	HYD unit pump	Kw / p	11 / 6		

FANUC No. of simultaneously controlled axis: 2-axis

적	Length × Width × Height	mm	9300 × 3700 × 4400	9800 × 3700 × 4400	9300 × 4400
	Machine Net Weight	Kg	23000	25000	27000